



FLASH TEST REPORT

Execution

State of charge Date Executed by 24.3 % 05/06/2024 08:59:59

AURES Holdings

Vehicle

Brand Model VIN Mileage MG Automotive Marvel R - 69,9kWh LSJE24097PS022449 6,828 km

Analysis Result

AVILOO SCORE

100

High voltage battery usage and history

Analysis of charging & driving behavior

70 / 70

High voltage battery performance

Analysis of cell voltages and module temperatures.

30 / 30

High voltage battery control unit


Check of signals and calculations of the battery management control unit.



Vehicle communication interface

Check of communication via the diagnostic interface.





DI Wolfgang Berger MBA CSO and Founder

DI Nikolaus Mayerhofer CTO and Founder





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

08:59:56 AVILOO Box connected.

- FLASH Test started.
- Vehicle detected.
- Starting data acquisition.
- Finished data acquisition.
- Analyzing data.
- Analysis completed.

DETAILED RESULTS OF PERFORMED CHECK

Vehicle Information

VIN LSJE24097PS022449 Date 05/06/2024 08:59:59 Mileage 6,828 km

Measurements High Voltage System

Battery temperature 19 °C Maximum cell temperature deviation 0.5 °C 345.5 V Pack voltage Maximum cell voltage deviation 8.03 mV Peak current during check -3.56 A State of Health (SoH - read from car manufacturer) 100 %



Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h



^{*}The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.